



Mini-Brute 250 Automated Label Applicator



The **Mini-Brute 250** is an ideal label applicator for applying UPC Code and other labels that do not require precise placement. The economically priced Mini-Brute is perfect within production environments due to their compact size and ease of operation.

FEATURES:

Label Width Range of ½" to 2½"

Label Roll Size: 10" Max. O.D. on 3" Core

Standard Placement Accuracy: ±.125"

Easy to Use Operator Interface

Specifications :

- Aluminum construction with stainless steel fasteners.
- Controls and solid state circuitry contained within a moisture and dust resistant enclosure.
- Designed for continuous operation up to 100 labels/min (based on label size).
- 120 Volt AC, 5 amp.
- Operating temperature range; 40° F to 125° F (4.4 ° C to 51.6 ° C)
- Available in right or left hand configuration.
- User friendly electronic controls.
- Retro reflective product sensor.

Options

- Structural Steel tri-base with corrosion resistant finish
- Clear label sensor
- Hot stamp imprinters
- Servo Motor Drive
- Stepper Motor Drive
- Low label detection system
- Alarm light tree
- Product handling equipment

Label

- Standard ½" – 2½" label widths.
- Core size: 3" I.D.
- Die-cut, edge trimmed and waste removed with minimum 3/32" gap.
- 10" Supply roll.
- Opaque label.